SAFETY DATA SHEET

Print Date: 5/21/2019 Revision Date: 5/21/2019

1. IDENTIFICATION

| Product Description | Mississippi Rebels Red |
|---------------------|-------------------------|
| Trade Name | Polyester |
| Product # | COL1786326 |
| Supplier | Columbia Coatings |
| | 1173 Industrial Park Rd |
| | Columbia, TN 38401 |
| Contact | (931) 388-7730 Phone |
| | (931) 388-5573 Fax |

2. HAZARD IDENTIFICATION

Product is a mixture of hazardous and non-hazardous ingredients compounded in a polymer.

| *Information pertaining to particular |
|---|
| danger for man and environment. |
| -Harmful by inhalation and/or if swallowed. |





*Classification System

-Classification was made according to the latest editions of international substances lists, and expanded upon from company literature data.

| NFPA Ratings | Scale 0-4 |
|--------------|-----------|
| Health | 2 |
| Fire | 1 |
| Reactivity | 1 |

| HMIS Ratings | Scale 0-4 |
|--------------|-----------|
| Health | 1 |
| Fire | 1 |
| Reactivity | 1 |

3. Composition/information on ingredients

| Hazardous | Case# | PEL-OSHA | TLV-ACGIH | CONCENTRATE |
|--|------------|----------------------|------------------------|-------------|
| Components | | | | % |
| Barium Sulfate, Natural | 7727-43-7 | 5 mg/m ³ | 5 mg/m ³ | 25 – 50 |
| Titanium Dioxide | 13463-67-7 | 15 mg/m ³ | 10 mg/m ³ | < 2.5 |
| 1,3,5-tris(oxiranylmethyl)- 1,3,5-triazine- 2,4,6(1H,3H,5H)-trione | 2451-62-9 | n/a | 0.05 mg/m ³ | 2.5 - 10 |

4. FIRST AID MEASURES

*After Inhalation

-Supply fresh air and seek medical attention.

*After Skin Contact

-Generally the product does not irritate the skin but water and soap can be used for rinsing.

*After Eye Contact

-Rinse opened eye for several minutes under clean running water.

*After Swallowing

-Rinse mouth out and then drink water. If symptoms persist, seek medical attention.

5. FIRE FIGHTING MEASURES

*Suitable Extinguishing Agents

-Use CO2, extinguishing powder or water spray. Fight larger fires with water spray, alcohol, or resistant foam.

*Firefighting Instructions

-Use fully protective equipment with self-contained breathing apparatus.

*Explosion

-Avoid generating dust; fine dust dispersed in the air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.

*Personal Protective Equipment

-Wear self-contained respiratory device.

6. ACCIDENTAL RELEASE MEASURES

*Personal Related Safety Precautions

-Ensure adequate ventilation

*Measure for Environmental Protection

-Do not allow to enter sewer/surface or ground water.

*Measure for Cleaning and Collecting

-Pick up mechanically. Dispose contaminated material as waste according to item 13.

7. HANDLING AND STORAGE

*Information For Safe Handling

-Prevent formation of dust and ensure good ventilation/exhaustion at the workplace.

*Information About Protection Against Explosions and Fires

-Dust can combine with air in suspended form when applying and can be an explosive mixture.

*Requirements To Be Met By Storerooms and Receptacles

-Store in a cool, dry place in a tightly closed container. Storage temperatures not to exceed 25°C/77°F to ensure product quality. Shelf life of the product at that temperature is up to 2 years, after that, the performance of the products will deteriorate. Protect from heat and direct sunlight. Protect from humidity and water.

*Information About Storage In Once Common Storage Facility.

-Not Required

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

| O. LAI OSORE CONTROLS AND I ERSONAL I ROTECTION | | |
|--|---|--|
| *Additional Information About Design of Technical Systems | | |
| -No Data: See item 7. | | |
| *Components with Limited Values That May Require Monitoring at the Workplace. | | |
| -See product ingredients. | | |
| *Personal Protective Equipment | | |
| -Keep away from foods, beverages, animals and feed. Wash hands before breaks and at the end of work. The usual precautionary measures for handling chemicals should be followed. | | |
| Protective Equipment for | It is recommended to use MSHA approved respirator when handling | |
| Inhalation | powders. Powders are considered nuisance dust. | |
| Hygienic Measures for Skin | Avoid skin contact; use long sleeve shirts and impermeable gloves at | |
| Contact | a minimum when handling powders. TYVEK full body suits or | |
| | equivalent are recommended for heavy exposure. Be sure to launder | |
| | contaminated clothing before reuse. Wash skin with mild soap and | |
| | water if contact occurs. If symptoms continue seek medical | |
| | attention. | |
| Eye Protection | Require the use of safety goggles with side shields. Powder particles | |
| | can be abrasive on the cornea. In case of eye contact, flush with | |
| | plenty of fresh water. If irritation develops or persists, seek medical | |
| | attention | |

9. PHYSICAL AND CHEMICAL PROPERTIES

| Physical | | |
|------------------------|---|--|
| Form: | Solid, finely divided powder | |
| Color: | According to product specs | |
| Odor: | Nearly odorless | |
| Chemical | | |
| Specific Gravity: | Approx. 1.54 g/cm ³ | |
| Coverage: | 125 sq. ft / lb. | |
| Flash Point: | > 300°C (572°F) | |
| Hardness: | H - 2H (ASTM D3363) | |
| Danger of Explosion: | Dust at sufficient concentrations can form explosive mixtures with air. | |
| Density: | 1.2 - 1.9 g/cm ³ | |
| Solubility with Water: | Insoluble | |
| Solvent Content: | n/a | |
| Salt Spray: | 1000 hrs. less than 1/16" in creepage over B-1000 panels | |
| Film Thickness: | 2.5 – 3.5 mils | |
| Humidity: | 1000 hrs. no blistering | |
| Flexibility: | 3/16" (ASTM D522) | |
| Impact: | 160 in-lb. direct & reverse | |
| Cross Hatch Adhesion: | 5B (ASTM D3359) | |

10. STABILITY AND REACTIVITY

*Product Stability

-No decomposition if used according to specifications.

*Thermal Decomposition/Conditions To Be Avoided

-Decomposition at high temperatures may yield Carbon Dioxide, Carbon Monoxide, Nitrous Oxide and other hazardous gases.

*Dangerous Reactions

-N/A

*Dangerous Products of Decomposition

-N/A

11. TOXICOLOGICAL INFORMATION

*Primary Irritant Effect

-On the skin – Powder can be irritation through rubbing action, also has a drying effect.

-In the eye – Powder can be irritating through rubbing, can cause abrasion on the cornea.

*Sensitization

-Sensitization possible through skin contact.

*Additional Toxicological Information

-The product shows the following danger according to internally approved calculation methods for preparations: Harmful!

12. ECOLOGICAL INFORMATION

*General Notes

-Water hazard class 1 (Self-Assessment): Slightly hazardous for water.

13. DISPOSAL INFORMATION

*Packaging

-Disposal must be made according to official regulations.

14. TRANSPORTATION INFORMATION

*DOT Regulations

-Non-Hazardous / Non-Regulated

*Maritime Transportation IMDG

-Non-Polluting

15. REGULATIONS

*Product Related Hazard Information

-The product has been classified and marked in accordance with directives on hazardous materials.

*Hazard Symbols

-Harmful

*Hazard-Determining Components of Labeling

-N/A

*Risk Phrases

- -Harmful by inhalation and if swallowed.
- -May cause sensitization by skin contact.

*Safety Phrases

- -Keep out of reach of children.
- -Keep container dry.
- -Keep container in a well-ventilated area.
- -Keep away from food, drink and animals/feed.
- -Do not breath gas/fumes/vapors/spray.
- -If swallowed, seek medical advice immediately and show this label.

16. OTHER INFORMATION

THIS INFORMATION IS BASED ON OUR PRESENT KNOWLEDGE. HOWEVER, THIS DOES NOT CONSTITUTE A GUARANTEE FOR ANY SPECIFIC PRODUCT FEATURES AND SHALL NOT ESTABLISH A LEGALLY VALID CONTRACTUAL RELATIONSHIP.