

Columbia Coatings

Technical Data Sheet

Columbia Coatings
1173 Industrial Park Rd
Columbia, TN 38401
931-388-7730
931-388-5573 FAX



Number:	NPCS
Name:	Nanner Peel Chemical Stripper
Type:	Liquid Stripper

Chemical Properties

Appearance	Amber clear liquid
Odor	Mild
pH	1-2

Recommended Application

Step #1	Prepare a strip tank with lid and proper ventilation.
Step #2	Submerge parts in solution (can be diluted up to 50%).
Step #3	Recommended dwell time is 20 minutes in heated bath (dwell time may vary). For best results heat solution to 165-175 °F
Step #4	Rinse parts using fresh water and pressure washer.

Benefits

- Especially designed for aluminum and non-ferrous metals. Can be used on ferrous metals. Please use extra caution as it can be damaging to certain magnesium alloys.
- No methylene chloride- safe for use.
- Low vapor pressure reduces VOC's, Environmentally friendly

Health and Safety

- Please refer to SDS for complete health and safety information.

Storage

- Store in a dry location at room temperature. Keep container closed and maintain all original markings and labels. Keep this container and vapors from this container away from heat, sparks, flame, and other ignition sources. Recommended storage in ferrous, stainless steel and plastic containers only. Note: do not store in aluminum containers at any time.

www.columbiacoatings.com