



SAFETY DATA SHEET

Section 1 – Identification

Product Identifier: HHBL Metallic Ceramic Coating

Other means of identification: Not Available

Part Number: HHBL

Product Type: Liquid

Recommended Use: Thermal Barrier Corrosion resistance

Restrictions on Use:

Manufacturer / Supplier:

Tech Line Coatings, Inc
PO Box 668, 10840 Chapman, Seymour, TN 37865
USA
Phone/Fax 1-865-773-0599
www.techlinecoatings.com

Industrial Use Only

Keep out of reach of children.

Emergency Phone: N. America +1-800-535-5053
Intl. +1-352-323-3500

Section 2 – Hazards Identification

OSHA status: This material is considered hazardous by the OSHA Hazard Communication Standard (29CFR 1910.1200)

Classification of the substance or mixture: Acute Toxicity (Oral) – category 4
Carcinogenicity - category 1A
Not Corrosive

Signal Word: Warning

Hazard Statements: Harmful if swallowed. May cause cancer



Symbols:

Precautionary statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not eat, drink or smoke while using this product. Wash hands thoroughly after handling.

Response: If exposed or concerned: get medical attention. If Swallowed: Immediately call a poison center or a physician. Rinse mouth.

Storage: Store locked up

Disposal: Dispose with container and contents in accordance with all Local, State, National and international standards.

Hazards not otherwise classified: None known

Section 3 – Composition / Information On Ingredients

Product Code: CermaKrome

Table with 4 columns: Component Name, Common Name / Synonyms, CAS#, % of Weight. Rows include Water, Phosphoric Acid, Chromium Trioxide, and Cobalt Aluminate Blue spinel.

Cobalt metal,dust and fumes (as Co)

Components not listed above are non-hazardous.

Testing to US Department of Transportation (DOT) and International Dangerous Goods codes show that HHBL is not regulated for shipping.

Section 4 – First Aid Measures

**General advise:**

- Consult a physician. Show this Safety Data Sheet to the doctor in attendance. Move out of dangerous area.

**After EYE Contact:**

- Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

**After SKIN Contact:**

- Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

**After INHALATION:**

- Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**After SWALLOWING:**

- Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Most important symptoms/effects, acute and delayed**

**Inhalation:** No known significant effects or critical hazards.

**Ingestion:** Harmful if swallowed.

**Skin contact:** No known significant effects or critical hazards.

**Eye contact:** No known significant effects or critical hazards.

**Over-exposure signs/symptoms**

**Eye contact:** No specific data

**Inhalation:** No specific data.

**Indication of immediate medical attention and special treatment needed, if necessary**

**Notes to physician:** Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled

**Specific treatments:** No specific treatment

**Protection of first-aiders:** No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See section 11 for additional information

**Section 5 – Fire Fighting Measures**

---

Not Flammable

**Extinguishing Media:**

- Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable Media:**

- None Known

**Special Fire Fighting Procedures:**

- Use full protective equipment, including self contained breathing apparatus

**Unusual Fire And Explosion Hazards:**

- During emergency conditions, overexposure to decomposition products may cause a health hazard.

**Specific Hazards Arising from the Chemical:**

- Water runoff can cause environmental damage, dike and collect water used to fight fire.
- In a fire or if heated, a pressure increase will occur and the container may burst

**Decomposition products may include the following materials:**

- metal oxide/oxides
- phosphorus oxides

**Special protective actions for fire-fighters :**

- Special protective actions for fire-fighters: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters:**

- Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## **Section 6 – Accidental Release Measures**

### **Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel:** No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment

**For emergency responders :** If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non emergency personnel".

**Environmental precautions:** Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### **Methods and materials for containment and cleaning up:**

**Small spill:** Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor

**Large spill:** Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Additional Information:

- See Section 7 for safe handling information.
- See Section 8 for PPE information
- See Section 13 for disposal information

## **Section 7 – Handling And Storage**

### **Precautions for safe handling**

**Protective measures:** Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene:** Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Conditions for safe storage, including any incompatibilities:** Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully

resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

**Conditions for safe storage:** Store at 55-90°F (13-32°C).

**SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION**

Component	ACGIH TLV	OSHA PEL	NIOSH REL
Phosphoric Acid	1 mg/m3	1 mg/m3	1 mg/m3
Chromium Trioxide	0.5 mg/m3	0.005mg/m3	0.001 mg/m3
Cobalt Aluminate Blue Spinel Cobalt metal,dust and fumes(as Co)	TWA 0.02 mg/m3 (as Co)	TWA 0.1 mg/m3 ( as Co) dust and fume	TWA 0.05 mg/m3 (as Co) Dust and fume

**Appropriate engineering controls:** If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits

**Environmental exposure controls:** Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels

**Individual protection measures:**

**Hygiene measures :** Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection:** Safety eyewear complying with an approved standard should be used to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

**Skin protection:**

**Hand protection:** Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product

**Other skin protection:** Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection:** Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

---

Form :	liquid
Color :	Blue
Odor :	Slightly musty smell to no odor
Odor Threshold:	Not Established
pH :	1.8 to 2.6
Melting point / Freezing point:	Not Established
Initial boiling point :	Not Established
Flash point :	> 212° F (Water based)
Evaporation Rate:	Not Established
Upper/lower flammability or explosive limits:	Not Established
Vapor pressure	Not Established
Vapor density	Not Established
Relative density	Not Established
Solubility(ies)	Water: somewhat soluble
Partition coefficient: n-octanol/water	Not Established
Auto-ignition temperature	Not Established
Decomposition temperature	Not Established
Viscosity	Not Established
Total VOC	0 lbs/gal

## SECTION 10 STABILITY AND REACTIVITY

---

Reactivity	No data available on mixture
Chemical stability	Stable
Possibility of hazardous reactions	No data available on mixture
Conditions to avoid (e.g., static discharge, shock, or vibration)	No data available on mixture
Incompatible materials	Magnesium, strong alkali's, strong reducing agents, strong oxidizing agents.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous products should not be produced.

## SECTION 11 TOXICOLOGICAL INFORMATION

---

**Carcinogenicity:** Not available.

### Classification

Product/ingredient name	OSHA	IARC	NTP
<b>Chromium (VI) trioxide</b>	<b>+</b>	<b>1</b>	<b>Known to be a human carcinogen</b>

**Mutagenicity:** Not available.

**Teratogenicity:** Not available

**Reproductive toxicity:** Not available.

**Specific target organ toxicity (single exposure):** Not available

**Specific target organ toxicity (repeated exposure):** Not available

**Aspiration hazard:** Not available

**Information on the likely routes of exposure: Routes of entry anticipated: Oral, Dermal, Inhalation.**

**Inhalation :** No known significant effects or critical hazards.

**Ingestion :** Harmful if swallowed.

**Skin contact** : No known significant effects or critical hazards.

**Eye contact** : Contact with eyes may cause irritation.

**Symptoms related to the physical , chemical and toxicological characteristics**

**Eye contact:**Contact with eyes may cause irritation.

**Inhalation:** Can cause irritation to nose and throat. Symptoms may include runny nose , sneezing, coughing, itching, and a burning sensation.

**Skin contact:** No specific data

**Ingestion:** No specific data

**Delayed and immediate effects and also chronic effects from short and long term exposure**

**Short term exposure:**

**Potential immediate effects:** Not available.

**Potential delayed effects :** Not available.

**Long term exposure:**

**Potential immediate effects:** Not available.

**Potential delayed effects :** Not available.

**Potential chronic health effects:**

Not available

**General** : No known significant effects or critical hazards.

**Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : No known significant effects or critical hazards.

**Acute Toxicity**

Phosphoric Acid	Oral LD50	LD50 Oral - rat – 1,530 mg/kg
	Inhalation LC50	LC50 - rabbit – 5.337 mg/l Exposure time: 1 h
	Dermal LD50	LD50- rabbit – 1,260 mg/kg
Chromium Trioxide	Oral LD50	LD50 Oral - rat - male and female - 52 mg/kg
	Inhalation LC50	LC50 Inhalation - rat - male - 4 h - 217 mg/m3
	Dermal LD50	LD50 Dermal - rabbit - male and female - 57 mg/kg
Cobalt Aluminate Blue Spinel	Oral LD50	LD50 Oral - rat - > 10000 mg/kg
	Inhalation LC50	LD50 Inhalation - rat - 4 h - >11.1 mg/l
	Dermal LD50	No data available

**Skin Corrosion/Irritation:**

This mixture has been tested using the Corrositex test method in compliance with EPA method 1120, and the OECD Guideline For The Testing Of Chemicals number 435, and found to be **not** corrosive.

**Carcinogenicity**

IARC: 1 - Group 1: Carcinogenic to humans (Chromium trioxide)

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: Known to be human carcinogen (Chromium trioxide)

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

This product contains a component that has been reported to be carcinogenic based on its IARC, ACGIH, NTP, or EPA classification.

## SECTION 12 ECOLOGICAL INFORMATION

---

**General Comments:** Do not allow material to be released into the environment without proper governmental permits

### Environmental Toxicity:

#### Phosphoric Acid

Toxicity to fish	LC50: 75.1 mg/l Exposure time: 96 h Species: Oryzias latipes (Japanese medaka)
Toxicity to daphnia and other aquatic invertebrates	EC50: 376 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea)
Toxicity to algae	EC50: 32 mg/l Exposure time: 72 h Species: Pseudokirchneriella subcapitata (green algae)

#### Chromium Trioxide

Toxicity to fish	LC50 - Tilapia mossambica - 21.05 - 141.38 mg/l - 96.0 h LC0 - Leuciscus idus (Golden orfe) - 100 mg/l - 48.0 h
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia magna (Water flea) - 0.8 mg/l - 48 h

#### Cobalt Aluminate Blue Spinel

Toxicity to fish, daphnia and other aquatic invertebrates	No Data Available
---	-------------------

**Persistence and degradability:** no data available

### Bioaccumulative potential:

Product/ingredient name	LogPow	BCF	Potential
Water	-1.38	-	low

**Mobility in soil:** no data available

**Other adverse effects:** no data available

## SECTION 13 DISPOSAL CONSIDERATIONS

---

### Waste Disposal Method:

Disposal should be made in accordance with federal, state and local regulations. Recovered non-usable material is a RCRA hazardous waste. Treatment, storage, transportation and disposal must be in accordance with EPA and State regulation under the authority of the Resource Conservation and Recovery Act (RCRA) 40 CFR parts 260-271. A competent and properly permitted contractor should do appropriate disposal.

## SECTION 14 TRANSPORTATION INFORMATION

---

### Non-Hazardous for Shipping:

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage

## SECTION 15 REGULATIONS

---

### Other Regulations, Limitations, and Prohibitive Regulations:

#### International Inventories

All of the components in this product are on or exempt from the following inventories:

USA (TSCA), CANADA (DSL / NDSL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (ECL), China (IECSC), Japan (ENCS), Philippines (PICCS).

#### International Inventory Legend

TSCA: US - Toxic Substance Control Act

DSL: Canada - Domestic Substance List

NDSL: Canada - Non-Domestic Substance List  
 IECSC: China - Inventory of Existing Chemical Substances China  
 EINECS: EU Inventory of Existing Commercial Chemical Substances  
 ELINCS: EU List of Notified Chemical Substances  
 ECL: Korea - Existing Chemicals List  
 AICS: Australia - Inventory of Chemical Substances  
 ENCS: Japan - Existing and New Chemical Substances  
 PICCS: Phillipines - Inventory of Chemicals and Chemical Substances

## SECTION 15 REGULATIONS

---

### U.S. Regulations:

Component	SARA 302	SARA 311 / 312	SARA 313	Massachusetts RTK	Pennsylvania RTK	New Jersey RTK	California Prop 65 list
Phosphoric Acid	No	Yes	No	Yes	Yes	Yes	No
Chromium Trioxide	No	Yes	Yes	Yes	Yes	Yes	Yes
Barium*						Yes	
Copper*						Yes	
Nickel*				Yes	Yes		Yes
Arsenic*				Yes			
Cadmium*				Yes			
Cobalt*							Yes

\*Components of the Cobalt Aluminate Blue Spinel

**SARA 311 / 312 Hazards:** Acute Health Hazard, Chronic Health Hazard

## SECTION 16 OTHER INFORMATION

---

Date Prepared: May 8, 2015

Update: Dec. 27, 2017

THIS INFORMATION IS FURNISHED WITHOUT WARRANTY, REPRESENTATION, INDUCEMENT OR LICENSE OF ANY KIND, EXCEPT THAT IT IS ACCURATE TO THE BEST OF TECH LINE COATINGS, INC., KNOWLEDGE OR OBTAINED FROM SOURCES BELIEVED BY TECH LINE COATINGS, INC. TO BE ACCURATE, AND TECH LINE COATINGS, INC., DOES NOT ASSUME ANY LEGAL RESPONSIBILITY FOR USE OR RELIANCE UPON SAME. BEFORE USING ANY CHEMICAL, READ ITS LABEL, INSTRUCTIONS AND SAFETY DATA SHEET.